

**018F6251** **Solenoid coil, BF230AS, Cable, 1.00 m, Supply voltage [V] AC: 220 - 230, Multi pack**

Electrical connection: Cable, Supply voltage [V] AC: 220 - 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

**PRODUCT DETAILS**

<b>Gross weight</b>	0.354 Kg
<b>Net weight</b>	0.297 Kg
<b>Volume</b>	0.86 Liter
<b>EAN</b>	5702428024815
<b>Actuator size</b>	13.5 mm
<b>Ambient temperature range [°C] [max]</b>	80 °C
<b>Ambient temperature range [°C] [min]</b>	-40 °C
<b>Ambient temperature range [°F] [max]</b>	175 °F
<b>Ambient temperature range [°F] [min]</b>	-40 °F
<b>Approval</b>	LLC CDC TYSK
<b>Cable diameter [mm]</b>	6.6 mm
<b>Cable length [in]</b>	40 in
<b>Cable length [m]</b>	1 m
<b>China RoHS compliance</b>	Out of scope
<b>Coil connection</b>	Cable
<b>Coil design standard</b>	VDE 0580
<b>Coil fastening</b>	Clip-on
<b>Coil winding insulation class</b>	Class H to IEC 85
<b>Colour</b>	Blue
<b>Compliance</b>	EN 60730-1
<b>Conductor area [mm<sup>2</sup>]</b>	3 x 0.75 mm <sup>2</sup>
<b>Duty rating</b>	Continuous
<b>Electrical connection</b>	Cable
<b>Electrical connector</b>	3 core cable
<b>Enclosure rating IP</b>	IP67
<b>EU RoHS compliance</b>	Out of scope
<b>Frequency [Hz]</b>	50 Hz
<b>Identical product</b>	018F8201
<b>In scope of WEEE and contain batteries</b>	No
<b>Packing format</b>	Multi pack
<b>Parts Program name</b>	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22

## PRODUCT DETAILS

	EV220B 65 - 100
	EV222B
	EV224B
	EV227B
	EV250B
	EV251B
<b>Power consumption 50Hz [VA]</b>	22 VA
<b>Power consumption [W] 50Hz</b>	12 W
<b>Product accessories</b>	Solenoid coil accessories
<b>Product group</b>	Solenoid valves
<b>Product Name Description</b>	Solenoid coil
<b>Quantity per packing format</b>	24 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>Rel. Humidity [% RH] [max]</b>	100 %
<b>Rel. Humidity [% RH] [min]</b>	0 %
<b>SCIP dossier no.</b>	23785618-b379-4da7-a913- ecd40c8fae6d
<b>Serviceable</b>	No
<b>Spare part number</b>	018F6251
<b>Supply voltage 50Hz Max [V]</b>	230 V
<b>Supply voltage 50Hz Min [V]</b>	220 V
<b>Supply voltage [V] AC [max]</b>	230 V
<b>Supply voltage [V] AC [min]</b>	220 V
<b>Type</b>	BF230AS
<b>Type designation</b>	BF230AS
<b>UK RoHS compliance</b>	Out of scope

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)